

Material Safety Data Sheet



Spray Wax

1. Product and company identification

Product name	: Spray Wax
Material uses	: Drying agent.
Supplier/Manufacturer	: Les Savons Evy Inc. 3460, 39th Avenue Montreal, QC, H1A 3V1 Tel : (514) 642-9920 Toll free : 1-800-715-6687 Fax : (514) 642-4278 Email : info@savonevy.com
Responsible name	: Atrion Regulatory Services, Inc.
In case of emergency	: CANUTEC (613) 996-6666

2. Hazards identification

Physical state	: Liquid.
Odor	: Characteristic.
Emergency overview	: DANGER! MAY BE FATAL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. Very toxic by inhalation. Harmful in contact with skin and if swallowed. Irritating to eyes, respiratory system and skin. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Contains material that can cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects	
Inhalation	: Very toxic by inhalation. Irritating to respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	: Toxic if swallowed.
Skin	: Toxic in contact with skin. Irritating to skin.
Eyes	: Irritating to eyes.
Potential chronic health effects	
Chronic effects	: Contains material that can cause target organ damage.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which causes damage to the following organs: blood, kidneys, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Over-exposure signs/symptoms	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing

2. Hazards identification

- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
- See toxicological information (section 11)

3. Composition/information on ingredients

Name	CAS number	%
2-Butoxyethanol	111-76-2	1 - 5
Isopropyl alcohol	67-63-0	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention.
- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
- Ingestion** : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

- Flammability of the product** : No specific fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Product name

2-Butoxyethanol

Exposure limits

CA Alberta Provincial (Canada, 10/2006). Skin
8 hrs OEL: 97 mg/m³ 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).
TWA: 20 ppm 8 hour(s).

CA Ontario Provincial (Canada, 3/2007). Skin
TWAEV: 20 ppm 8 hour(s).

CA Quebec Provincial (Canada, 12/2006).
TWAEV: 20 ppm 8 hour(s).

Isopropyl alcohol

CA Alberta Provincial (Canada, 10/2006).
15 min OEL: 1230 mg/m³ 15 minute(s).
8 hrs OEL: 400 ppm 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).
TWA: 200 ppm 8 hour(s).
STEL: 400 ppm 15 minute(s).

CA Ontario Provincial (Canada, 3/2007).
TWAEV: 200 ppm 8 hour(s).

8 . Exposure controls/personal protection

STEV: 400 ppm 15 minute(s).
CA Quebec Provincial (Canada, 12/2006).
 TWAEV: 400 ppm 8 hour(s).
 STEV: 500 ppm 15 minute(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes : Splash goggles.

Skin : Lab coat.

Respiratory : Vapor respirator.

Hands : Nitrile gloves.

Personal protective equipment (Pictograms) :



HMIS Code/Personal protective equipment : G

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state : Liquid.

Color : Amber.

Odor : Characteristic.

Boiling/condensation point : 79°C (174.2°F)

Melting/freezing point : <4°C (<39.2°F)

Relative density : 0.95

10 . Stability and reactivity

Stability : The product is stable.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : No specific data.

Materials to avoid : Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10 . Stability and reactivity

Conditions of reactivity : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Species	Dose	Result	Exposure
Isopropyl alcohol	Rabbit	12800 mg/kg	LD50 Dermal	-
	Rat	5045 mg/kg	LD50 Oral	-
2-Butoxyethanol	Rat	5000 mg/kg	LD50 Oral	-
	Rabbit	220 mg/kg	LD50 Dermal	-
	Rat	917 mg/kg	LD50 Oral	-
	Rat	470 mg/kg	LD50 Oral	-

Inhalation : Very toxic by inhalation. Irritating to respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion : Toxic if swallowed.

Skin : Toxic in contact with skin. Irritating to skin.

Eyes : Irritating to eyes.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
2-Butoxyethanol	A3	3	-	-	-	-
Isopropyl alcohol	A4	3	-	-	-	None.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Test	Species	Exposure	Result
Isopropyl alcohol	-	Crustaceans	48 hours	Acute LC50 1400000 to 1950000 ug/L
	-	Fish	96 hours	Acute LC50 >1400000 ug/L

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

AERG : Not applicable.
Regulatory information
TDG / IMDG/ IATA : Not regulated.

15 . Regulatory information

Canada

WHMIS (Canada) : Class D-1A: Material causing immediate and serious toxic effects (Very toxic).
 Class D-2B: Material causing other toxic effects (Toxic).



Canadian lists : **CEPA Toxic substances:** None of the components are listed.
Canadian ARET: None of the components are listed.
Canadian NPRI: The following components are listed: 2-Butoxyethanol; Isopropyl alcohol
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.

Canada inventory (DSL/NDL) : **Canada inventory:** All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists : This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

16 . Other information

Label requirements : MAY BE FATAL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Hazardous Material Information System (U.S.A.) :

Health	*	2
Fire hazard		0
Physical Hazard		0
Personal protection		G

HAZARD RATINGS


- 4- Extreme
- 3- Serious
- 2- Moderate
- 1- Slight
- 0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :

16 . Other information



References : ANSI Z400.5, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005.

Date of issue : 2011/12/12

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.